

Claims 1-10 have been cancelled.

11. (currently amended)      A fixture for forming unit loads to be received on two or more loading ledges, which unit loads after forming are lifted from the fixture together with the loading ledges, wherein the fixture has an approximate rectangular frame, formed of at least two parallel long struts and at least two parallel short struts at the ends of the long struts, wherein transversal bars are arranged moveable on the long struts, with the ends of each bar on each long strut and wherein feet of the loading ledges are received in cups arranged on the fixture, at least some of which cups are arranged moveable and lockable on the transversal bars ~~is to receive the loading ledges and the fixture has means to adapt the positions of the loading ledges depending on the size and form of the unit loads to be formed.~~

12. (cancelled)

13. (currently amended)      The fixture of claim ~~12~~ 11, wherein a further number of intermediate, short struts are arranged between the long struts.

14. (cancelled)

15. (cancelled)

16. (currently amended)      The fixture of claim ~~15~~ 11, wherein two cups are arranged on each transversal bar.

17. (currently amended)      The fixture of claim ~~15~~ 11, wherein four transversal bars are received on the frame.

18. (currently amended)      The fixture of claim ~~15~~ 11, wherein each movable cup has a support, having legs straddling a transversal bar and a locking screw received in an opening of one of the legs of the support.

19. (currently amended)      The fixture of claim ~~14~~ 11, wherein each transversal bar has supports straddling the long sides of the frame and the supports having locking means to lock the position of the transversal bar.

20. (cancelled)